

**JP10036569A 19980210 THERMOPLASTIC ELASTOMER COMPOSITION**

**Assignee/Applicant:** YOKOHAMA RUBBER CO LTD **Inventor(s)** : IGAWA KATSUHIRO ;

ADACHI NAOYA ; OZAWA OSAMU **Priority (No,Kind,Date)** : JP19041296 A 19960719 X

**Application(No,Kind,Date):** JP19041296 A 19960719 **IPC:** 6C 08L 21/00 A **Language of**

**Document:** NotAvailable **Abstract:**

**PROBLEM TO BE SOLVED:** To obtain a thermoplastic elastomer composition which attains both high flexibility and low permanent compression strain, and provide a car lamp structure using the same.

**SOLUTION:** This elastomer composition contains the following components (A) and (B) at a weight ratio of A/B is 15/85-80/20 and is prepared by adding 5-100 pts.wt. of component (C) to 100 pts.wt. of the total components (A)+(B) after dynamic vulcanization. The objective car lamp structure is manufactured at least partially from this elastomer composition: Component (A): a thermoplastic resin having a softening point of  $\geq 100^{\circ}\text{C}$  and a melting point of  $\leq 250^{\circ}\text{C}$ ; Component (B): an at least partially vulcanized rubber composition; and Component (C): a petroleum softening agent and/or a plasticizer.

**Legal Status:** There is no Legal Status information available for this patent